



Specifications Noxion LED Downlight  
Slim V2.0 20W 2000lm 120D - 830  
Warm White | 225mm - Cutout  
200mm - IP44 - Emergency 3H

[View Product](#)

General Information

|                          |                                                                                      |
|--------------------------|--------------------------------------------------------------------------------------|
| SKU                      | 238918                                                                               |
| EAN                      | 8719157015073                                                                        |
| Brand                    | Noxion                                                                               |
| Manufacturer Name        | Noxion LED Downlight Slim V2.0 IP44 20W 3000K Cutout Ø200mm<br>Frame Ø225mm w/ EM3HR |
| Any Lamp all-in warranty | 6 Years                                                                              |
| Average Lifetime (h)     | 50000                                                                                |

Technical Information

|                             |                     |
|-----------------------------|---------------------|
| Emergency Lighting          | With Emergency Unit |
| Tiltable                    | No                  |
| Technology                  | LED Integrated      |
| Wattage                     | 20                  |
| Voltage (V)                 | 220-240             |
| Dimmable                    | Not Dimmable        |
| Colour Code                 | 830 Warm White      |
| Colour temperature (Kelvin) | 3000 Warm White     |
| Colour Rendering (Ra)       | 80-89               |
| Colour of Light             | White               |
| Light colour options        | Single Color        |
| Driver Included             | Yes                 |

|                          |                                       |
|--------------------------|---------------------------------------|
| Beam Angle (degree)      | 120                                   |
| Luminous Flux (Lumen)    | 2000                                  |
| Luminous Efficacy (lm/W) | 100                                   |
| Power factor             | >0.90                                 |
| Installation Depth (mm)  | 19                                    |
| Unified Glare Rating     | < 28 - for hallways and storage rooms |
| Optical Cover            | PC (Polycarbonate)                    |
| Product Type Category    | LED Downlight                         |

## Fixture Information

|                        |                   |
|------------------------|-------------------|
| Mounting Method        | Recessed          |
| Cut out (mm)           | 200               |
| IP-rating              | IP44              |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Operating Temperature  | -20 to +40        |
| Housing                | Aluminium         |
| Colour of the Fixture  | White             |
| Colour of material     | White             |
| Series                 | Slim              |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 26  |
| Diameter (mm) | 225 |

 **Sensor Information**  **Customised quotation**

Type of sensor



Up to 7 years warranty

No Sensor



Easy return process