



Specifications Philips LED Panel  
Coreline RC132V 34.5W 4300lm - 840 -  
Cool White | 60x60cm - UGR <23



[View Product](#)

General Information

|                          |                                        |
|--------------------------|----------------------------------------|
| SKU                      | 246031                                 |
| EAN                      | 8719514950351                          |
| Brand                    | Philips                                |
| Manufacturer Name        | RC132V G5 31_36_43S/840 PSU W60L60 NOC |
| Any Lamp all-in warranty | 5 Years                                |
| Average Lifetime (h)     | 50000                                  |
| Series                   | RC132V                                 |

Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Technology                  | LED Integrated  |
| Replaces (Watt)             | 4x18            |
| Wattage                     | 34.5            |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Not Dimmable    |
| Colour Code                 | 840 Cool White  |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra)       | 80-89           |
| Colour of Light             | White           |
| Light colour options        | Single Color    |
| Light Distribution          | Symmetrical     |

|                          |                   |
|--------------------------|-------------------|
| Luminous Flux (Lumen)    | 4300              |
| Luminous Efficacy (lm/W) | 125               |
| IP-rating                | IP44              |
| Impact Protection (IK)   | IK03 - 0.35 joule |
| Fixture Connection       | Terminal, 2-pole  |
| Driver Included          | Yes               |
| Power factor             | >0.90             |
| Product Type Category    | LED Panel         |

## Fixture Information

|                       |                          |
|-----------------------|--------------------------|
| Mounting Method       | Recessed                 |
| Unified Glare Rating  | < 23 - for general areas |
| Optical Cover         | PS (Polystyrene)         |
| Operating Temperature | -10 to +40               |
| Emergency Lighting    | No Emergency Unit        |
| Colour of the Fixture | White                    |
| Housing               | Steel                    |
| Colour of material    | White                    |

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 595     |
| Width (mm)     | 595     |
| Height (mm)    | 11      |

## Why Any-lamp?



Order from the **largest lighting specialist** in Europe



**Customised** quotation

## Sensor Information



Up to **7 years warranty**



**Easy** return process

|                |           |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|